



## The Kohler® Advantage

- **High Quality Power**  
Kohler home generators provide advanced voltage and frequency regulation along with ultra-low levels of harmonic distortion for excellent generator power quality to protect your valuable electronics.
- **Extraordinary Reliability**  
Kohler is known for extraordinary reliability and performance and backs that up with a 5-year or 2000 hour limited warranty.
- **Powerful Performance**  
Exclusive Powerboost™ technology provides excellent starting power. The Kohler 8 kW generator can easily start and run a 4 ton air conditioner with up to 4.5 kW preload.\*
- **Enclosure**  
Bold new Kohler design in steel, dipped in e-coat for extra corrosion protection and painted with a durable powder coat finish.
- **Quiet Operation**  
Kohler home generators provide quiet, neighborhood-friendly performance.

## Standard Features

- **DC2 Controller**
  - One digital controller manages both the generator set and Model RXT transfer switch functions
  - Designed for today's most sophisticated electronics.
  - Electronic speed control responds quickly to varying household demand.
  - Digital voltage regulation protects your sensitive electronics from harmonic distortion and unstable power quality.
  - Two-line, backlit LCD display with adjustable contrast is easy to read, even in direct sunlight or low light.
  - OnCue® Plus Generator Management System for remote monitoring is included with every generator.
- **Kohler Engine Features**
  - Kohler engine with efficient OHV design
  - Powerful, reliable air-cooled performance
  - Simple field conversion between natural gas and LPG fuels while maintaining emission certification
- **Designed for Easy Installation**
  - Steel base
  - Hinged, locking roof
  - Fuel and electrical connections through the enclosure wall eliminate the need for stub-ups through the bottom
  - Accepts natural gas fuel pressure as low as 3.5 inches
  - Load connection terminal block allows easy field wiring
  - Designed for outdoor installation only
- **Approved for stationary standby applications in locations served by a reliable utility source**
- **Model RXT Transfer Switch**
  - 100 amp ATS w/NEMA 1 enclosure with 12-space load center for indoor installation is included
  - See page 4 for additional information
- **Meets 181 mph wind rating**
- **Certifications**
  - Meets emission regulations for U.S. Environmental Protection Agency (EPA) 40 CFR 60 stationary source standards with both LPG and natural gas.  
**Note:** CARB does not regulate emergency standby generators outputting less than 50 HP. Only the EPA standards apply.
  - UL 2200 listed (60 Hz model)
  - Accepted by the Massachusetts Board of Registration of Plumbers and Gas Fitters.

## Generator Ratings

Model	Voltage	Phase	Hz	Alternator	Standby Ratings			
					Natural Gas		LPG	
					kW/kVA	Amps	kW/kVA	Amps
8RESVL	120/240	1	60	2F3	7/7	29.2	8/8	33.3

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO-3046/1, BS5514, AS2789, and DIN 6271. GENERAL GUIDELINES FOR DERATING: *ALTITUDE*: Derate 4% per 305 m (1000 ft.) elevation above 153 m (500 ft.). *TEMPERATURE*: Derate 2% per 5.5°C (10°F) temperature increase above 16°C (60°F). Availability is subject to change without notice. The generator set manufacturer reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever. Contact your local Kohler Co. generator distributor for availability.

\* Check the appliance manufacturer's specifications for actual power requirements. Consult a Kohler® Power Systems professional to calculate your exact residential power system requirements.

# Alternator Specifications

## Alternator Specifications

Specifications	PowerBoost™ Generator 1-Phase
Manufacturer	Kohler
Output reconnectable	120/240
Type	2-Pole, Rotating Field
Leads, quantity	4
Voltage regulator	Digital
Insulation:	NEMA MG1-1.66
Material	Class H
Temperature rise	Class H
Bearing: quantity, type	1, Sealed Ball
Coupling	Direct
Amortisseur windings	Full
Voltage regulation, no-load to full-load RMS	± 1.0%
One-step load acceptance	100% of Rating
Peak motor starting kVA:	(35% dip for voltages below)
240 V, 2F3 (60 Hz)	16.8

## Alternator Features

- Compliance with NEMA, IEEE, and ANSI standards for temperature rise
- Self-ventilated and drip-proof construction
- Windings are vacuum-impregnated with epoxy varnish for dependability and long life.
- Superior voltage waveform and minimum harmonic distortion from skewed alternator construction
- Digital voltage regulator with ±1.0% no-load to full-load RMS regulation
- Rotating-field alternator with static exciter for excellent load response
- Total harmonic distortion (THD) from no load to full load with a linear load is less than 5%

## Application Data

### Engine

Engine Specifications	
Manufacturer	Kohler
Engine: model, type	SV620
Cylinders	Single
Displacement, cm <sup>3</sup> (cu. in.)	597 (36.4)
Bore and stroke, mm (in.)	94 x 86 (3.7 x 3.44)
Compression ratio	8.5:1
Main bearings: quantity, type	2, Parent Material
Rated RPM	
60 Hz	3600
Max. engine power at rated rpm, kW (HP)	
LPG, 60 Hz	11 (14.8)
Natural gas, 60 Hz	8.5 (11.4)
Cylinder head material	Aluminum
Valve material	Steel
Piston type and material	Aluminum Alloy
Crankshaft material	Heat Treated, Ductile Iron
Governor: type	Electronic
Frequency regulation, no load to full load	Isochronous
Frequency regulation, steady state	±1.0%
Air cleaner type	Dry

### Engine Electrical

Engine Electrical System	
Ignition system	Electronic, Capacitive Discharge
Starter motor rated voltage (DC)	12
Battery (purchased separately):	
Ground	Negative
Volts (DC)	12
Battery quantity	1
Recommended cold cranking amps: (CCA) rating for -18°C (0°F)	500
Group size	51

### Lubrication

Lubricating System	
Type	Full Pressure
Oil capacity (with filter), L (qt.) *	1.5 (1.6)
Oil filter: quantity, type	1, Cartridge

\* Oil capacity for a new, dry engine.

### Fuel Pipe Size

Minimum Gas Pipe Size Recommendation, in. NPT			
Pipe Length, m (ft.)	Natural Gas 99,200 Btu/hr.	LPG 160,800 Btu/hr.	
8 (25)	3/4 in.	3/4 in.	
15 (50)	3/4 in.	3/4 in.	
30 (100)	1 in.	3/4 in.	
46 (150)	1 in.	1 in.	
61 (200)	1 in.	1 in.	

### Exhaust

Exhaust System	
Exhaust temperature exiting the enclosure at rated kW, dry, °C (°F)	190 (374)

## Fuel Requirements

Fuel System	
Fuel types	Natural Gas or LPG
Fuel supply inlet	1/2 NPT
Fuel supply pressure, kPa (in. H <sub>2</sub> O):	
Natural gas	0.87-2.7 (3.5-11)
LP	1.7-2.7 (7-11)

Fuel Composition Limits *	Nat. Gas	LPG
Methane, % by volume (minimum)	90 min.	—
Ethane, % by volume (maximum)	4.0 max.	—
Propane, % by volume	1.0 max.	85 min.
Propene, % by volume (maximum)	0.1 max.	5.0 max.
C <sub>4</sub> and higher, % by volume	0.3 max.	2.5 max.
Sulfur, ppm mass (maximum)	25 max.	
Lower heating value, MJ/m <sup>3</sup> (Btu/ft <sup>3</sup> ), (minimum)	33.2 (890)	84.2 (2260)

\* Contact your local distributor for suitability and rating derates based on fuel compositions outside these limits.

## Operation Requirements

Fuel Consumption			
Model	Fuel Type	% Load	Fuel Consumption, m <sup>3</sup> /hr. (cfh)
8RESVL	Natural Gas	100	2.8 (99)
		75	2.2 (78)
		50	1.8 (64)
		25	1.5 (54)
	LPG	Exercise	1.2 (42)
		100	1.8 (64)
		75	1.7 (58)
		25	1.3 (45)
		Exercise	1.0 (35)

Nominal fuel rating: Natural gas: 37 MJ/m<sup>3</sup> (1000 Btu/ft.<sup>3</sup>)  
LPG: 93 MJ/m<sup>3</sup> (2500 Btu/ft.<sup>3</sup>)

LPG conversion factors: 8.58 ft.<sup>3</sup> = 1 lb.  
0.535 m<sup>3</sup> = 1 kg  
36.39 ft.<sup>3</sup> = 1 gal.


## Sound Data

Model 8RESVL 8 point logarithmic average sound levels are 66 dB(A) during weekly engine exercise and 72 dB(A) during full-speed generator diagnostics and normal operation. The lowest point sound levels are 63 dB(A) and 68 dB(A) respectively as compared to competitor ratings.\*

All sound levels are measured at 7 meters with no load.

\* Lowest of 8 points measured around the generator. Sound levels at other points around generator may vary depending on installation parameters.

## DC2 Controller



The DC2 controller provides integrated control for the generator set, Kohler® Model RXT transfer switch, programmable interface module (PIM), and load control module (LCM).

The DC2 controller's 2-line LCD screen provides a clear, easy-to-read display of status messages, even in direct sunlight or low light.

## DC2 Controller Features

- OFF, AUTO, RUN, and EXERCISE pushbuttons
- LED indicators for OFF, AUTO, RUN, and EXERCISE modes
- LCD screen
  - Two lines x 16 characters per line
  - Backlit display with adjustable contrast for excellent visibility in all lighting conditions
- Scrolling system status display
  - Generator set status
  - Voltage and frequency
  - Engine temperature
  - Oil pressure
  - Battery voltage
  - Engine runtime hours
  - Maintenance reminders
  - OnCue® Plus status (connected/disconnected)
- Date and time displays
- Smart engine cooldown senses engine temperature
- Digital isochronous governor to maintain steady-state speed at all loads
- Digital voltage regulation: ± 1.0% RMS no-load to full-load
- Automatic start with programmed cranking cycle
- Exercise modes
  - Unloaded weekly exercise with complete system diagnostics
  - Unloaded full-speed exercise
  - Loaded full-speed exercise (Model RXT ATS required)
- Front-access mini USB connector for SiteTech™ or USB Utility connection
- Integral Ethernet connector for Kohler® OnCue® Plus
- Built-in 2.5 amp battery charger
- Remote two-wire start/stop capability for optional connection of Model RDT or RSB transfer switches
- Diagnostic messages
  - Displays diagnostic messages for the engine, generator, Model RXT transfer switch, programmable interface module (PIM), and load control module (LCM)
  - Over 70 diagnostic messages can be displayed
- A laptop computer and Kohler® SiteTech™ software can be used to change system settings or upgrade controller firmware.

## Generator Set Standard Features

- ATS: Model RXT automatic transfer switch with indoor enclosure and 12-circuit load center
- Battery cables
- Flexible fuel line
- Critical silencer
- DC2 generator set/ATS controller
- EPA certified fuel system
- Field-connection terminal block
- Fuel solenoid valve and secondary regulator
- Line circuit breaker: 40 Amps
- Multi-fuel system, LPG/natural gas, field-convertible
- Oil drain extension with shutoff valve
- OnCue® Plus Generator Management System
- Rodent-resistant construction
- Sound enclosure with sound-deadening, flame-retardant foam per UL 94, class HF-1
- 5-year limited warranty

## Model RXT Transfer Switch



- 100 amp RXT with 12-space load center and NEMA 1 steel enclosure for indoor installation
- UL listed
- 240 VAC/60 Hz
- Withstand rating 10,000 amps with specified breakers
- Designed for use only with Kohler® generator sets equipped with the RDC2 or DC2 controller
- See RXT Specification Sheet for more information

## Available Accessories\*

### Concrete Mounting Pads

- Concrete mounting pad, 3 in. thick
- Concrete mounting pad, 4 in. thick (recommended for storm-prone areas)

## Available Accessories, Continued

### Controller Accessories

- Programmable Interface Module (PIM) (provides 2 digital inputs and 6 relay outputs)
- Load Control Module (LCM) (provides 4 power relays and 2 HVAC relays)

### Electrical System

- Battery

### Maintenance

- Maintenance kit

### Literature

- General maintenance literature kit
- Overhaul literature kit
- Production literature kit

### Starting Aids

- Carburetor heater, 120 VAC (recommended for reliable starting at temperatures below 0°C [32°F])

### RXT Transfer Switch Accessories

- Status indicator

### Miscellaneous Accessories


- \_\_\_\_\_
- \_\_\_\_\_

\* Accessories are available through Kohler authorized distributors and dealers.

## Generator Set Dimensions and Weights

Overall Generator Size, L x W x H: 712 x 777 x 824 mm  
 (28 x 30 x 32.4 in.)

Shipping Weight:  
 8RESVL w/100 amp RXT ATS 181 kg (398 lb.)



NOTE: Dimensions are provided for reference only and should not be used for planning installation. Contact your local distributor for more detailed information.

**DISTRIBUTED BY:**