

FLAMELESS

MOBILE HEATERS

GENERAC
MOBILE



FLAMELESS MOBILE HEATERS

Generac Mobile flameless mobile heaters are designed to safely provide powerful heat in environments in which an open flame could be hazardous. Our patented user interface system is easy to use and allows you to set a temperature that will remain reliable and consistent. And as with all Generac Mobile heaters, our flameless heaters are built with safety in mind. Each unit is lockable, provides 110% containment, includes multiple safety alarms and the engine is protected because it is never loaded until it is warmed to the ideal level.

APPLICATIONS

- Gas and oil exploration
- Utilities and power plants
- Mining
- Painting and coatings
- Construction
- Pipeline projects
- Employee locker areas and housing
- Emergency thawing
- Pre-warming of equipment and motors
- Dehumidification
- Agricultural applications



MAC550F



MAC750F

	MAC400FHC	MAC550F	MAC750F	MAC950F
Engine				
	USA (METRIC)			
Make	Isuzu	Isuzu	Isuzu	John Deere
Model	4LE2X S253	4LE2X S253	4JJ1T	4045
EPA Tier	Final Tier 4	Final Tier 4	Final Tier 4	Final Tier 4
Max Speed: rpm	2500	2500	2000	2200
Max Engine Power - Standby: hp	62	62	73	139
Operating Speed: rpm	2400	2400	2000	2200
Capacities				
Heat Transfer Fluid: gal (L)	24 (90.85)	24 (90.85)	25 (94.64)	28 (105.99)
Fuel Tank: gal (L)	55 (208.2)	111 (420.18)	160 (605.67)	160 (605.67)
Max Fuel Consumption Rate: gph (Lph)*	3.2 (12.11)	3.2 (12.11)	3.55 (13.44)	TBA
Est. Run Time: hrs*	19	38	44	TBA



MAC950F

Additional options available

	MAC400FHC	MAC550F	MAC750F	MAC950F
Heater				
USA (METRIC)				
Heat Output: BTU*	448,000	448,000	512,400	994,000
Temperature Rise @ X°	180°F (82°C)	180°F (82°C)	180°F (82°C)	180°F (82°C)
Maximum Output Temperature	180°F (82°C)	180°F (82°C)	180°F (82°C)	180°F (82°C)
Duct Diameter: in (mm)	1 x 12 (304.8)	2 x 12 (304.8)	2 x 12 (304.8)	1 x 20 (508)
Duct Length: ft (m)	25 (7.62)	N/A	N/A	N/A
Estimated Heater Efficiency	85%	85%	85%	85%
Fan				
Air Flow: CFM	1400 - 3600	1400 - 3500	2650 - 5500	3000 - 6000
Pressure: in, H2O	9	5	5	5
Weights & Dimensions				
L x W x H: in (m)	120 x 54 x 82 (3.05 x 1.37 x 2.08)	171 x 72 x 81 (4.34 x 1.83 x 2.06)	178 x 72 x 80 (4.52 x 1.83 x 2.03)	191 x 72 x 88 (4.85 x 1.83 x 2.24)
Dry Weight: lbs (kg)	4360 (1978)	4480 (2032)	5540 (2513)	6330 (2871)
Operating Weight: lbs (kg)	4700 (2132)	5180 (2350)	6400 (2903)	7900 (3583)
Chassis				
Number of Axles	1	1	2	2
Axle Rating: lbs (kg)	6000 (2722)	6000 (2722)	6000 (2722)	6000 (2722)
Tire Size	4 x 8 x 16 in (101.6 x 203.2 x 406.4 mm)	235/80 R16	235/80 R16	225/75 R15
Maximum Tire Pressure: psi	80	80	80	80
Brakes	Tow Bar Activated	Electric	Electric	Electric
Hitch - Standard: in (mm)	Pintle	2-5/16 (58.74) Ball Coupler	2-5/16 (58.74) Ball Coupler	2-5/16 (58.74) Ball Coupler
Certifications				
CSA Listed	Yes	Yes	Yes	Yes

* This number has been calculated using the maximum fuel consumption at the full rated horsepower as provided by the engine manufacturer.

FLAMELESS MOBILE HEATERS



SAFETY ALARMS

- Low heat transfer fluid volume
- Low fuel
- High temperature
- Low heat transfer fluid pressure
- Positive air shutdown

When you need it, we bring the heat.



Learn more at GeneracMobileProducts.com

24/7 • 365 Nationwide Service Support Network;
because when you're on the job, we're on the job.



*Assembled in the USA using
domestic and foreign parts

Part No. 0202820 REV 01/2019
©2019 Generac Power Systems, Inc. All Rights Reserved.
Specifications are subject to change without notice.

GENERAC[®]
MOBILE

Generac Mobile Products LLC
215 Power Drive, Berlin, WI 54923
GeneracMobileProducts.com | 800-926-9768 | 920-361-4442